



Dimensions


MultiCyclone 12 Plus



MultiCyclone 16 Plus



Head Loss Curves



Warranty

MultiCyclone Plus is covered by a 2 year warranty and 1 year warranty on labour. Commercial installations are covered by a 1 year warranty.

www.poolspamartindonesia.com

WATERCO | **CENTRAL**
water the liquid of life | INDONESIA

MULTI CYCLONE PLUS

A revolution in pool filtration



MultiCyclone Plus combines centrifugal and cartridge filtration into one streamline housing, creating an ultra compact filtration system that can be vertically installed on a pool pump.

- Dual stage filtration
- Ultra compact
- Ease of maintenance
- Save time, water and energy

MULTI CYCLONE 12 PLUS

MULTI CYCLONE 16 PLUS



SHOW ROOM & MARKETING

POOLSPA MART INDONESIA

Jl. Bulevar Selatan, Bekasi Utara, Summarecon
Mobile : 0818-919-597
website : poolspamartindonesia.com

HEAD OFFICE & SERVICE CENTRE

PT. PERSADA CAHAYA MULIA INDONESIA

website : www.watercocentral.com

WATERCO | **CENTRAL**
water, the liquid of life | INDONESIA




enviropo
SAVE TIME, WATER AND ENERGY

www.watercocentral.com

Dual stage filtration

Incoming water tangentially enters its multiple hydrocyclones, generating a strong centrifugal effect. Approximately 80% of the incoming dirt load is spiralled down to its clear sediment chamber. The outgoing water is finally polished via its inbuilt cartridge filter, producing crystal clear water.



Extended filter capacity

As MultiCyclone Plus's centrifugal section filter pre-filters up to 80% of the incoming dirt load, the capacity of its 40 ft² filter cartridge is magnified by up to 5 times.

Ease of maintenance

MultiCyclone Plus's sediment chamber is easily cleaned by opening its purge valve. Only 15 litres of water is discharged.



Ultra compact

MultiCyclone Plus's streamlined design means the entire filtration system can be installed vertically, reducing the footprint of the equipment pad. Additionally, minimal pipework reduces the filtration system's overall head loss. Alternatively the MultiCyclone Plus can be installed next to the pump by using an optional support base.



Note: It is recommended when installing the MultiCyclone Ultra directly to the pump as illustrated, the MultiCyclone Ultra should be supported to ensure stability.


MultiCyclone Support Stands

The MultiCyclone has two purpose designed support stands to suit all MultiCyclone models and most installations.



MultiCyclone Stand MKII, is a great option if the height of the installation is prohibitive.

Dimension



Note: MultiCyclone Support Stand is suitable for most Waterco Domestic Pool Pumps. Excluding Hydrostar & all Commercial Pumps.

Specifications

Model	Hydrocyclones	Connection Ports	Minimum Flow	Maximum Flow	Filter Area	Maximum Pool Size	Maximum Pressure
MultiCyclone12 Plus	12	40mm / 1 1/2"	40lpm	152lpm	3.7m² / 40 sqft	73,000l	350 kPa (50psi)
MultiCyclone16 Plus	16	50mm / 2"	50lpm	152lpm	3.7m² / 40 sqft	73,000l	350 kPa (50psi)

Maximum flow is limited by the surface area of the filter cartridge. Residential Cartridge Design Filtration Rate: 41 lpm/m² (1gpm/ft²)